

### Bulletin 1/2025 Supplement to the Regulations 2025

The amendment is valid with immediate effect.

Changes made as follows:

- Deletions are printed in '**Bold**', '*Italics*' and crossed out (~~word~~).
- Additions are printed in '**Bold**' and '*Italics*'.

Approved by KNAF  
permit: 0323.25.255  
date: 31-07-2025

### Technical Regulations 2025 Porsche Sprint Challenge Benelux

#### 31. Table 4 - max. permissible thicknesses of the spacer washers

Car Type	Front	Rear
Porsche 911 GT3 Cup, type 992 + ABS	20,0mm	15,0mm
Porsche 911 GT3 Cup, type 991 Gen II + ABS	18,0mm	15,0mm
Porsche 911 GT3 Cup, type 991 Gen I + ABS		
Porsche 718 Cayman GT4 RS Clubsport, type 982	18,0mm	18,0mm
Porsche 718 Cayman GT4 Clubsport MR, type 982 (with air intake)		
Porsche 718 Cayman GT4 Clubsport MR, type 982 (without air intake)		
Porsche 718 Cayman GT4 Clubsport, type 982 (Trophy Spec)		
Porsche Cayman GT4 Clubsport, type 981		

For the competition at Zandvoort, **Zolder & Spa Francorchamps** the maximum permissible combined thickness of the spacer washers in the front and rear axle control arms off all GT3 Cup Cars are:

- Front axle: 19.0 mm
- Rear axle: 13.0 mm

and for all GT4 Clubsport Cars are:

- Front axle: 18.0 mm
- Rear axle: 10.0 mm